

ngplastics,corp

PRODUCT: RPET Green Strapping

FEATURES:

- Excellent chemical & weather resistance
- Good Tensile Strength
- Safe & convenient for operation
- Good for the environment

| Width (mm) | (inch) | Thickness (mm) | (inch) | Breaking Strength (lbs) | (N) | Length per Roll (ft) | (m) |
|------------|--------|----------------|--------|-------------------------|------|----------------------|------|
| 12.0 | 0.47 | 0.6 | 0.02 | 607 | 2700 | 8,050 | 2450 |
| 12.0 | 0.47 | 0.65 | 0.025 | 675 | 3000 | 7,000 | 2150 |
| 13.0 | 0.51 | 0.6 | 0.02 | 675 | 3000 | 7,500 | 2300 |
| 13.0 | 0.51 | 0.7 | 0.028 | 765 | 3400 | 6,000 | 1900 |
| 14.0 | 0.55 | 0.7 | 0.028 | 855 | 3800 | 6,000 | 1850 |
| 15.0 | 0.59 | 0.7 | 0.028 | 877 | 3900 | 5,500 | 1650 |
| 16.0 | 0.63 | 0.65 | 0.025 | 900 | 4000 | 5,000 | 1500 |
| 14.0 | 0.55 | 0.75 | 0.03 | 921 | 4100 | 5,000 | 1600 |
| 16.0 | 0.63 | 0.8 | 0.032 | 1124 | 5000 | 4,500 | 1300 |
| 16.0 | 0.63 | 0.9 | 0.035 | 1213 | 5400 | 4,000 | 1250 |
| 16.0 | 0.63 | 1 | 0.04 | 1349 | 6000 | 3,500 | 1020 |
| 19.0 | 0.75 | 0.8 | 0.032 | 1394 | 6200 | 3,500 | 1100 |
| 19.0 | 0.75 | 1 | 0.04 | 1574 | 7000 | 3,500 | 1000 |

| | |
|----------------------|---------|
| Dia. Of Core (inch): | 16x6 |
| (mm): | 406x152 |
| Roll Weight (lbs): | 44 |
| (kgs): | 20 |